Water-based stretching liquid CUT-523B

[Product performance]

CUT-523B water-based stretching fluid, this product is specially designed for the stretching process of ferrous metal steel materials. This product has excellent anti-rust effect on iron, pig iron, ferroalloy, cast iron, steel and other materials, and has strong extreme pressure lubricity. The surface of the stretched workpiece has high brightness and is easy to clean.



Cremfutssa CUT-524 現化油 記述

18L/barrel





dremfu 俊辅

Undiluted solution After diluted with water

[Product parameters]

200L/barrel

Test items	parameter
Appearance of original solution	Brown, transparent
density	0.88-0.92 g⋅cm³(20°)
concentration	≥80
pH value	8±0.5
Appearance of diluent	milky

Address: 1206, Baihui Center, Chang'an Town, Dongguan City



[Usage]

1. The oil tank or oil tank should be cleaned before using this product. It is strictly prohibited to mix it with other oil products. It should be stirred evenly before use.

2. Water-to-water ratio: direct raw solution stretching or water-to-water ratio: raw solution: water = 1: (1-5)

3. The working fluid concentration should not be less than 5. The appropriate working fluid concentration should be adjusted according to different anti-rust requirements.

[Packaging specifications]

18L/plastic bucket, 200L/large iron bucket.