

# CUT-523Emulsifiable oil universal cutting fluid

#### [Product performance]

CUT-523 Emulsifiable Oil Universal Cutting Fluid is a versatile cutting fluid designed for multi-purpose use. It offers excellent rust prevention and lubrication for ferrous metals, copper, and aluminum alloys. With low odor, low foaming, and skin-friendly properties, this product significantly extends the lifespan of cutting tools, eliminating the hassle of frequent oil changes. It's like a personal nurse for metal processing.



200L/drum



base oil after dilution with water

## [product parameters]

testing items	parameters
appearance of the base oil	brown
density	0.88-0.92 g⋅cm³(20°)
concentration	≥80
PH value	8±0.5

Address: 1206, Baihui Center, Chang'an Town, Dongguan City



appearance of the diluted solution

Milky white

### [usage method]

1. Before using this product, ensure the oil tank or reservoir is thoroughly cleaned. Mixing with other oils is strictly prohibited. Stir well before use.

2、 Dilution ratio: Base oil: Water = 1:(1-20).

3. The concentration of the working fluid should not be lower than 5. Adjust the concentration of the working fluid appropriately according to different processing techniques. For harder materials, dilute with 1-5 times water, and for softer materials, dilute with 5-20 times water.

#### [packaging specifications]

18L per plastic drum, 200L per large iron drum