

Ceramic cutting fluid DK-760C5

[Performance and use]

Dremfu DK-760C5 water-soluble grinding fluid is prepared by a variety of surfactants, lubricants, anti-rust agents and other additives. Suitable for ceramic material cutting, cutting, grinding, engraving and other cooling processing.

[Product advantage]

- 1. Excellent lubricity, cooling and cleaning.
- 2. Environmentally friendly and not harmful to skin.
- 3. Excellent powder sedimentation.
- 4. not corrupt, long service life.

[Main technical parameters]

item	Technical indicators	Technical indicators
External view	Light yellow transparent	Light yellow transparent
	liquid	liquid
pH value	9.5 ± 0.5	9.5 ± 0.5
Defoaming (ml)	2 or less	2 or less
Specific weight (g/ml)	1.10 ± 0.10	1.10 ± 0.10
Surface tension (dyn/cm)	30 or less	30 or less
Storage stability	conjunctive	conjunctive
corrosiveness	Grade A cast iron	Grade A cast iron
Rust resistance	Grade A cast iron	Grade A cast iron

[Instruction]

The working liquid is diluted with 10-20 times tap water or deionized water.

During use, the working liquid consumed can be supplemented at a concentration of 3-5%. Avoid mixing with other oils.

Effective Auxiliary Industrial Lubricants



[Packaging]

18L/ barrel, 25L/ barrel, 200L/ barrel.

[Note]

- 1. This product should not be mixed with other emulsions, semi-synthetic liquids, and fully synthetic liquids, because even if the system contains a small amount of rotten residual liquid, it will affect the use effect of the new liquid.
- 2.the production batch is not the same, the cutting fluid may have color differences, does not affect the normal use.