

# Synthesis of high temperature chain oil KT-08

## 【Product composition】

Dremfu synthetic high temperature chain oil KT-08 adopts refined synthetic base oil to add high temperature antioxidant, anti-wear, anti-rust and other additives through high temperature heating and preparation, high temperature does not drop oil, does not accumulate carbon, small volatilization, suitable for use temperature -15°C-330°C.

## 【Product use】

This product is suitable for high temperature transport bearings and transmission chains (such as paint production line chain, coating equipment, drying room, glass factory transport belt bearings, etc.) and polypropylene bidirectional film stretching machine, SMT production line. Lubrication of track chains of heat setting machines (tensioning machines) and SST resin finishing machines for the textile printing and dyeing industry.

## 【Product advantage】

1. Excellent high temperature oxidation stability, not easy to coking, less carbon deposit, can keep the chain clean for a long time, improve production efficiency.
2. Biodegradable, less evaporation loss, less oil, no pollution to the environment, meet the requirements of energy saving and environmental protection.
3. Good low temperature fluidity, good low temperature start-up of the machine in winter.
4. Good viscosity and temperature, good high temperature lubrication, effectively reduce chain wear, can withstand heavy load.

## 【Main technical parameters】

Model number	appearance	Density @15°C kg/l	Pour point °C	Viscosity 40°C mm <sup>2</sup> /s	Flash point (open cup)°C
KT-08	Yellow transparent liquid	0.85	-15	472	330

## 【Instruction】

1. This product is a direct use lubricant, do not need to add water, directly add recycling can be used.
2. Can be sprayed with automatic refueling machine, can also be brushed with a brush.

**【Note】**

1. Different brands, different quality, different models of high temperature oil, can not be mixed.
2. Please clean the lubricating part before using high temperature oil, and then apply the best.

**【Packaging】**

Unified packaging specifications, new white or yellow plastic packaging drums: 5KG/ drum, 15KG/ drum