

## Cutting fluid DK-760C6

### 【 Performance and use 】

Dremfu DK-760C6 water-soluble grinding fluid is prepared by a variety of surfactants, lubricants, anti-rust agents and other additives. It is suitable for wire-cut cooling processing of glass-ceramics, quartz, optical glass and other materials.

### 【 Main technical parameters 】

item	Technical indicators	Test method
External view	Light yellow transparent liquid	Eye survey
pH value	9.5 ± 0.5	GB6144-85
Defoaming (ml)	2 or less	GB6144-85
Specific weight (g/ml)	1.10 ± 0.10	hydrometer
Surface tension (dyn/cm)	30 or less	GB6144-85
Storage stability	conjunctive	GB6144-85
corrosiveness	Grade A cast iron	GB6144-85
Rust resistance	Grade A cast iron	GB6144-85

### 【 Product advantage 】

- Excellent lubricity, cooling and cleaning.
- Environmentally friendly and not harmful to skin.
- Excellent powder sedimentation.
- not corrupt, long service life.

### 【 Instruction 】

1. The working liquid is diluted with 10-20 times tap water or deionized water.
2. During use, the working liquid consumed can be supplemented at a concentration of 3-5%.
3. Avoid mixing with other oils.

**【 Packaging 】**

18L/ barrel, 25L/ barrel, 200L/ barrel.

**【 Note 】**

1. This product should not be mixed with other emulsions, semi-synthetic liquids, and fully synthetic liquids, because even if the system contains a small amount of rotten residual liquid, it will affect the use effect of the new liquid.

2.the production batch is not the same, the cutting fluid may have color differences, does not affect the normal use.