

# DZ series spindle oil

## [Product performance]

Junfu DZ series spindle oil is formulated with highly refined mineral oil as the base and a variety of efficient additives, including detergents, dispersants, anti-wear, anti-oxidation, anti-corrosion, and anti-foam agents. The product features low viscosity, excellent heat dissipation, and effectively removes heat generated during high-speed spindle operation. It has good oxidative stability, long service life, and excellent lubrication, rust prevention, corrosion resistance, and anti-foam properties, minimizing foam generation during circulation.

## [Product parameter]

item	DZ series spindle oil					
Model number	DZ-2#	DZ-5#	DZ-7#	DZ-10#	DZ-15#	DZ-22#
Kinematic viscosity (40 $^{\circ}$ C), mm2/s	2.210	5.002	7.132	10.04	14.89	22.86
Pour point, ° C	-24	-26	-19	-20	-15	-13
Open flash point, ° C	102	132	146	154	160	172
Closed flash point, ° C	80	98	-	-	-	-
Moisture, %	none	none	none	none	none	none
Mechanical impurity	qualifie	qualified	qualified	qualified	qualified	qualified

Tel :0769-85354390 E-mail: <u>2851953130@qq.com</u> Address: 1206 Baihui Center, Chang 'an Town,

**Dongguan City** 



#### [Performance features]

- \*Excellent Lubrication:\* The spindle oil contains multiple anti-wear additives that provide effective lubrication on all spindle components, protecting them from wear.
- \*Good Oxidation Resistance:\* It prevents the formation of deposits within closed circulation systems, avoiding damage to spindles and bearings and ensuring equipment precision.
- \*Rust Prevention:\* The spindle oil has strong rust and corrosion resistance, effectively inhibiting corrosion caused by moisture ingress.
- \*Good Cooling Performance:\* It has effective heat dissipation properties, quickly removing the heat generated during high-speed spindle operation.
- \*Good Cleanliness:\* It protects machine tool precision by preventing the formation of sludge and deposits over long-term use, ensuring effective flushing and stable spindle operation.

## [Scope of application]

• Suitable for textile machine, worsted spindle, automatic machine tool spindle and light load hydraulic circulation system, light load high speed industrial textile bearings, industrial circulation system, etc.

# [Packing specification]

18L/ plastic bucket, 200L/ large iron bucket.