

K-LS801 Copper Drawing Oil

【Product Performance】

K-LS801 Copper Drawing Oil is specifically developed for the drawing and forming of copper tubes. This oil contains various extreme pressure, lubrication, and rust prevention additives, offering good adhesion and strong lubrication properties. It ensures a high surface gloss of the workpieces and provides excellent protection for molds. It is suitable for the drawing and stamping processing of brass tubes, red copper tubes, and other copper tubes.

【product parameters】

project	typical data
kinematic viscosity at 40°C (mm ² /s)	30~35
flash point (°C)	>180
pour point (°C)	-10
Corrosion (100°C, 3H) steel, copper	qualified
mechanical impurities	qualified
moisture	无
appearance	yellow transparent

* The above parameters are for reference only. Please adjust them according to the actual processing conditions of your company as needed."

【performance characteristics】

1. Lubrication: Good adhesion, strong lubricating ability, providing a good surface gloss for processed parts, while offering excellent protection for tools;
2. Corrosion Resistance: Neutral formula provides effective protection for metals, preventing corrosion and discoloration;
3. Low viscosity oil, easy to clean.

【packaging specifications】

18L/ plastic drum, 200L/ large iron drum.

【Application Range 】

It is suitable for the drawing and stamping processing of brass tubes, red copper tubes, and other copper tubes.